



## TECHNICAL DATA

# HYPERTOUCH

EMOTIONAL SURFACES

A BRAND OF  IRIS CERAMICA GROUP

## BXICG-B640

KNX Power Supply 640mA

technical support: [hypertouch@iris-group.it](mailto:hypertouch@iris-group.it)

Via Radici Nord, 112 - 42014 Castellarano (RE) IT

AC 100VAC – 240VAC  
(50/60Hz)

Input Output Voltage 29V +/-1V

Power 18W

Nominal Output Current 640mA

Fuse 2A fast



## OPERATING PARTS

1. KNX bus terminal.
2. Power ON Led.
3. AC input power screw terminals (L,N,E).
4. Under cover Reset Switch and Fuse.

## INSTALLATION

1. Connect KNX bus to plug 1.
2. Connect AC power cable with Line (L), Neutral (N) and Earth (E).
3. Wait until Led On.

## DATA SHEETS



Operating Instructions  
for authorized electricians

## IMPORTANT SAFETY NOTES

Power Supply is equipped with Soft Start, a slow rate start up, in order to load in circuit capacitor without lowering output voltage.

Soft Start prevents damages caused by blackout. Start-up needs around 8 seconds.

Installation and commissioning of the device can only be carried out by authorized electricians. The relevant standards, directives, regulations and instructions must be observed. The device has the CE mark.